

# BLACK & DECKER GLOSS WHITE

## SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product identifier**

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	BLACK & DECKER GLOSS WHITE
Product Code	32420

**Relevant identified uses of the substance or mixture and uses advised against**

Identified Use(s)	Spray Paint
Uses Advised Against	None

**Company Identification**

Mr. Brands LLC  
113 Fillmore St.  
Bristol, PA 19007

**Telephone**

877-420-7555

**Fax**

215-633-8615

**E-Mail (competent person)**

mrbrands@mrbrands.com

**Emergency telephone number**

Emergency Phone No.

**Transportation Emergency:** CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)

### SECTION 2: HAZARDS IDENTIFICATION

**Classification of the substance or mixture**

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Liquefied gas; Skin Irrit. 2; Eye Irrit. 2; Skin Sens. 1B; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1

**Label elements**

Hazard Symbol



Signal word(s)

**DANGER**

Hazard Statement(s)

Extremely flammable aerosol.  
Pressurised container: May burst if heated.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
Suspected of damaging fertility or the unborn child.  
May cause drowsiness or dizziness.  
May be fatal if swallowed and enters airways.  
May cause damage to organs through prolonged or repeated exposure (Inhalation - neuropsychological effects, auditory dysfunction and effects on colour vision)

# BLACK & DECKER GLOSS WHITE

## Precautionary Statement(s)

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
 No smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Wash hands and exposed skin after use.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 Contaminated work clothing should not be allowed out of the workplace.

## Other hazards

Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Acetone	20 - 50	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Propane	15 - 20	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
Toluene	5-10	108-88-3	Flam. Liq. 2; H225 Repr. 2; H361 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Asp. Tox. 1; H304 STOT SE 3; H336 STOT RE 2; H373 Aquatic Acute 2; H401 Aquatic Chronic 3; H412
Butane	10 - 15	106-97-8	Flam. Gas 1; H220 Press. Gas (*)
Aliphatic Hydrocarbon	5-10	64742-49-0	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H336
Ethyl benzene	< 1	100-41-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 Asp. Tox. 1; H304 STOT RE 2; H373 Aquatic Acute 2; H401 Aquatic Chronic 3; H412
Titanium dioxide	0.002 - 11	13463-67-7	Not classified as dangerous for supply/use.
polymer	5-12	9038-95-3	Not classified as dangerous for supply/use.

Additional Information - None

\* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

## SECTION 4: FIRST AID MEASURES



Description of first aid measures

# BLACK & DECKER GLOSS WHITE

Inhalation	Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.
Skin Contact	Wash affected skin with soap and water. If symptoms develop, obtain medical attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.
Ingestion	Do not give anything by mouth to an unconscious person. Seek medical treatment. Do NOT induce vomiting.

**Most important symptoms and effects, both acute and delayed**

May be harmful if swallowed and enters airways.

**Indication of any immediate medical attention and special treatment needed**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

## SECTION 5: FIRE-FIGHTING MEASURES

**Extinguishing Media**

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

**Special hazards arising from the substance or mixture**

Highly flammable vapor (flash point below 23°C).

**Advice for fire-fighters**

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Avoid breathing vapors.

**Environmental precautions**

Prevent liquid entering sewers, basements and work pits.

**Methods and material for containment and cleaning up**

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

**Reference to other sections**

None

**Additional Information**

None

## SECTION 7: HANDLING AND STORAGE

**Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only. Avoid breathing spray.

**Conditions for safe storage, including any incompatibilities**

- Storage temperature

Keep in a cool, well ventilated place. Store at temperatures not exceeding 50 °C / 122 °F.

- Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

**Specific end use(s)**

Spray paint

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits**

# BLACK & DECKER GLOSS WHITE

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Acetone	67-64-1	1000 ppm	500 ppm	-----	750 ppm	^NIC
Toluene	108-88-3	200 ppm	20 ppm	300 ppm*	-----	*10-min. Ceiling
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#
Ethyl benzene	100-41-4	100 ppm	20 ppm	----	-----	----

^NIC = Notice of Intended Changes (ACGIH®); #Assure minimum oxygen content of work atmosphere. @Comply with OSHA 29 CFR 1910.1026 regarding Hexavalent Chromium.

## Recommended monitoring method

NIOSH 1300 (Ketones I); NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1501 (Hydrocarbons, Aromatic); NIOSH 1401 (Alcohols II), NIOSH 1550 (Naphthas)

## Exposure controls

### Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

### Personal protection equipment

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber or Butyl rubber). Use gloves only once. Check with protective equipment manufacturer's data.

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

## Environmental Exposure Controls

Prevent liquid entering sewers, basements and work pits.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance

Aerosol spray

Color.

Various

Odor

Hydrocarbon

Odor Threshold (ppm)

Not available

pH (Value)

Not available

Melting Point (°C) / Freezing Point (°C)

Not available

Boiling point/boiling range (°C):

Not available

Flash Point (°C)

Not available

# BLACK & DECKER GLOSS WHITE

Evaporation Rate	Not available
Flammability (solid, gas)	Extremely flammable aerosol.
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapor pressure (Pascal)	ca. $95 \times 10^4$ (Propane)
Vapor Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	Not available
Decomposition Temperature (°C)	Not available
Kinematic Viscosity	<20 mm <sup>2</sup> /s @ 40°C
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
<b>Other information</b>	Not available

## SECTION 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	Stable under normal conditions.
<b>Chemical stability</b>	Stable.
<b>Possibility of hazardous reactions</b>	None anticipated.
<b>Conditions to avoid</b>	Avoid contact with heat and ignition sources.
<b>Incompatible materials</b>	Strong oxidizing agents
<b>Hazardous decomposition product(s)</b>	Carbon monoxide, Carbon dioxide, Acrid smoke

## SECTION 11: TOXICOLOGICAL INFORMATION

**Exposure routes:** Inhalation, Skin Contact, Eye Contact

### Information on toxicological effects

Acetone (CAS No. 67-64-1)

#### Acute toxicity

Oral LD50 = 5800 mg/kg (rat)  
 Dermal LD50 >15800 mg/kg (rabbit)  
 Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness.

#### Irritation / Corrosivity

Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.

#### Sensitisation

It is not a skin sensitiser.

#### Repeated dose toxicity

Oral NOAEL = 900 mg/kg/day (rat) (90-days)  
 Inhalation NOAEL  $\geq$  19,000 ppm (rat)

#### Carcinogenicity

It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

#### Mutagenicity

Negative

#### Toxicity for reproduction

Negative

#### Other information

None known.

Toluene (CAS No. 108-88-3)

#### Acute toxicity

Oral LD50 = 5580 mg/kg (rat)  
 Dermal LD50 >5000 mg/kg (rabbit)  
 Inhalation LC50 (4 hour(s)) 28.1 mg/l (rat) - Vapours may cause drowsiness and dizziness.

#### Irritation / Corrosivity

Causes serious eye irritation. Causes skin irritation.

#### Sensitisation

It is not a skin sensitiser.

#### Repeated dose toxicity

Inhalation NOAEC = 1131 mg/m<sup>3</sup> (rat), 2 Year(s) - May cause damage to organs through prolonged or repeated exposure:

# BLACK & DECKER GLOSS WHITE

neuropsychological effects, auditory dysfunction and effects on colour vision.

## Carcinogenicity

It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

## Mutagenicity

There is no evidence of mutagenic potential.

## Reproductive toxicity

Suspected of damaging the unborn child. NOAEC: 2.8 mg/liter (rat)

### Aliphatic Hydrocarbon (CAS No. 64742-49-0) - By analogy with similar materials:

#### Acute toxicity (calculated / estimated)

Oral: LD50 >5000 mg/kg-bw  
 Dermal: LD50 >2000 mg/kg-bw  
 Inhalation: LC0 ≥5.28 mg/l (Vapor), 4-hr. rat - May cause drowsiness or dizziness.

#### Irritation/Corrosivity

Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

#### Sensitization

It is not a skin sensitizer.

#### Repeated dose toxicity

Oral: NOEL 750 mg/kg  
 Dermal: NOEL 0.5 ml/kg bw  
 Inhalation: NOEL ≥1000 mg/m<sup>3</sup>

## Carcinogenicity

It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

## Mutagenicity

Not to be expected

## Reproductive toxicity

Not to be expected

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

#### Aliphatic Hydrocarbon (CAS No. 64742-49-0) - By analogy with similar materials:

Short term	LC50 (96 hour): 2.5 mg/L (fish) EC50 (48 hour): 1.4 mg/L (crustacea) EC50 (72 hour): 1.3 mg/L (algae)
Long Term	NOEC (28 days): 0.098 mg/L (fish) LOEC (21 days): 1.2 mg/L (crustacea) LOEL (72 hour): 1 mg/L (algae)

#### Toluene (CAS No. 108-88-3)

Acute toxicity	LC50 (96 hour): 5.5 mg/l ( <i>Oncorhynchus kisutch</i> ) EC50 (48 hour): 3.78 mg/l ( <i>Ceriodaphnia dubia</i> ) EC50 (3 hour): 134 mg/l (Algae)
Long Term Toxicity	NOEC (40 days): 1.39 mg/l ( <i>Oncorhynchus kisutch</i> ) NOEC (7 days): 0.74 mg/l ( <i>Ceriodaphnia dubia</i> )
Persistence and degradability	Biodegradable
Bioaccumulative potential	The product has no potential for bioaccumulation.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

# BLACK & DECKER GLOSS WHITE

## SECTION 13: DISPOSAL CONSIDERATIONS

### Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

## SECTION 14: TRANSPORT INFORMATION

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:	Not applicable		

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Acetone	67-64-1	20-50	5000
Toluene	108-88-3	0-22.32	1000
Methyl Ethyl Ketone	78-93-3	0-7	5000
Ethyl benzene	100-41-4	0.35-0.759	1000

SARA 311/312 - Hazard Categories:

Fire  Sudden Release  Reactivity  Immediate (acute)  Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
Toluene	108-88-3	0-22.32
Ethyl benzene	100-41-4	0.35-0.759

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
Toluene	108-88-3	Developmental, Female Reproductive
Ethyl benzene	100-41-4	Cancer

\*Trace to none.

## SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: April 29,2024

# BLACK & DECKER GLOSS WHITE

## Hazard Statement(s) and Risk Phrases Listed in: SECTION 3:

### Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapor.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H336: May cause drowsiness or dizziness.
- H361: Suspected of damaging fertility or the unborn child.
- H373: May cause damage to organs through prolonged or repeated exposure.
- H400: Acute to aquatic life.
- H401: Toxic to aquatic life.
- H412: Harmful to aquatic life with long lasting effects.

**Training advice:** None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.