

BLACK & DECKER FLAT WHITE

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	BLACK & DECKER FLAT WHITE
Product Code	32432

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Spray Paint
Uses Advised Against	None

Company Identification	Mr. Brands LLC 113 Fillmore St. Bristol, PA 19007
------------------------	---

Telephone	877-420-7555
Fax	215-633-8615
E-Mail (competent person)	mrbrands@mrbrands.com

Emergency telephone number

Emergency Phone No.	Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)
---------------------	---

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)	Flam. Aerosol 1; Liquefied gas; Skin Irrit. 2; Eye Irrit. 2; Skin Sens. 1B; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1
-----------------------------	--

Label elements

Hazard Symbol



Signal word(s)

DANGER

Hazard Statement(s)

Extremely flammable aerosol.
Pressurised container: May burst if heated.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
May cause damage to organs through prolonged or repeated exposure (Inhalation - neuropsychological effects, auditory dysfunction and effects on colour vision)

BLACK & DECKER FLAT WHITE

Precautionary Statement(s) Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Wash hands and exposed skin after use.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Avoid breathing dust/fume/gas/mist/vapours/spray.
 Contaminated work clothing should not be allowed out of the workplace.

Other hazards Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Acetone	35 - 50	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Propane	12-18	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
Toluene	5-10	108-88-3	Flam. Liq. 2; H225 Repr. 2; H361 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Asp. Tox. 1; H304 STOT SE 3; H336 STOT RE 2; H373 Aquatic Acute 2; H401 Aquatic Chronic 3; H412
Butane	10 - 15	106-97-8	Flam. Gas 1; H220 Press. Gas (*)
Aliphatic Hydrocarbon	5-10	64742-49-0	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H336
Ethyl benzene	< 1	100-41-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 Asp. Tox. 1; H304 STOT RE 2; H373 Aquatic Acute 2; H401 Aquatic Chronic 3; H412
Titanium dioxide	0.002 - 11	13463-67-7	Not classified as dangerous for supply/use.
Talc	2-8	14807-96-6	Acute Tox. 4; H332 Eye Irrit. 2; H319
polymer	5-12	9038-95-3	Not classified as dangerous for supply/use.

Additional Information - None

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

BLACK & DECKER FLAT WHITE

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation	Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.
Skin Contact	Wash affected skin with soap and water. If symptoms develop, obtain medical attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.
Ingestion	Do not give anything by mouth to an unconscious person. Seek medical treatment. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

May be harmful if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

Special hazards arising from the substance or mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Avoid breathing vapors.

Environmental precautions

Prevent liquid entering sewers, basements and work pits.

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections

None

Additional Information

None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only. Avoid breathing spray.

Conditions for safe storage, including any incompatibilities

- Storage temperature

Keep in a cool, well ventilated place. Store at temperatures not exceeding 50 °C / 122 °F.

BLACK & DECKER FLAT WHITE

-Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

Specific end use(s)

Spray paint

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Acetone	67-64-1	1000 ppm	500 ppm	-----	750 ppm	^NIC
Toluene	108-88-3	200 ppm	20 ppm	300 ppm*	-----	*10-min. Ceiling
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#
Talc	14807-96-6	20 mppcf	2 mg/m3	----	----	----
Ethyl benzene	100-41-4	100 ppm	20 ppm	----	-----	----

^NIC = Notice of Intended Changes (ACGIH®); #Assure minimum oxygen content of work atmosphere. ®Comply with OSHA 29 CFR 1910.1026 regarding Hexavalent Chromium.

Recommended monitoring method

NIOSH 1300 (Ketones I); NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1501 (Hydrocarbons, Aromatic); NIOSH 1401 (Alcohols II), NIOSH 1550 (Naphthas)

Exposure controls

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Personal protection equipment

Eye/face protection

Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber or Butyl rubber). Use gloves only once. Check with protective equipment manufacturer's data.



Respiratory protection

Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.



Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

Prevent liquid entering sewers, basements and work pits.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

BLACK & DECKER FLAT WHITE

Appearance	Aerosol spray
Color.	Various
Odor	Hydrocarbon
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Extremely flammable aerosol.
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapor pressure (Pascal)	ca. 95 x 10 ⁴ (Propane)
Vapor Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	Not available
Decomposition Temperature (°C)	Not available
Kinematic Viscosity	<20 mm ² /s @ 40°C
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Other information	Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	Strong oxidizing agents
Hazardous decomposition product(s)	Carbon monoxide, Carbon dioxide, Acrid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Acetone (CAS No. 67-64-1)

Acute toxicity	Oral LD50 = 5800 mg/kg (rat) Dermal LD50 >15800 mg/kg (rabbit) Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness.
Irritation / Corrosivity	Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.
Sensitisation	It is not a skin sensitiser.
Repeated dose toxicity	Oral NOAEL = 900 mg/kg/day (rat) (90-days) Inhalation NOAEL ≥ 19,000 ppm (rat)
Carcinogenicity	It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity	Negative
Toxicity for reproduction	Negative
Other information	None known.

Toluene (CAS No. 108-88-3)

BLACK & DECKER FLAT WHITE

Acute toxicity Oral LD50 = 5580 mg/kg (rat)
 Dermal LD50 >5000 mg/kg (rabbit)
 Inhalation LC50 (4 hour(s)) 28.1 mg/l (rat) - Vapours may cause drowsiness and dizziness.

Irritation / Corrosivity Causes serious eye irritation. Causes skin irritation.

Sensitisation It is not a skin sensitiser.

Repeated dose toxicity Inhalation NOAEC = 1131 mg/m³ (rat), 2 Year(s) - May cause damage to organs through prolonged or repeated exposure: neuropsychological effects, auditory dysfunction and effects on colour vision.

Carcinogenicity It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity There is no evidence of mutagenic potential.

Reproductive toxicity Suspected of damaging the unborn child. NOAEC: 2.8 mg/liter (rat)

Aliphatic Hydrocarbon (CAS No. 64742-49-0) - By analogy with similar materials:

Acute toxicity (calculated / estimated) Oral: LD50 >5000 mg/kg-bw
 Dermal: LD50 >2000 mg/kg-bw
 Inhalation: LC0 ≥5.28 mg/l (Vapor), 4-hr. rat - May cause drowsiness or dizziness.

Irritation/Corrosivity Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

Sensitization It is not a skin sensitizer.

Repeated dose toxicity Oral: NOEAL 750 mg/kg
 Dermal: NOEAL 0.5 ml/kg bw
 Inhalation: NOAEL ≥1000 mg/m³

Carcinogenicity It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity Not to be expected

Reproductive toxicity Not to be expected

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Aliphatic Hydrocarbon (CAS No. 64742-49-0) - By analogy with similar materials:

Short term LC50 (96 hour): 2.5 mg/L (fish)
 EC50 (48 hour): 1.4 mg/L (crustacea)
 EC50 (72 hour): 1.3 mg/L (algae)

Long Term NOEC (28 days): 0.098 mg/L (fish)
 LOEC (21 days): 1.2 mg/L (crustacea)
 LOEL (72 hour): 1 mg/L (algae)

Toluene (CAS No. 108-88-3)

Acute toxicity LC50 (96 hour): 5.5 mg/l (*Oncorhynchus kisutch*)
 EC50 (48 hour): 3.78 mg/l (*Ceriodaphnia dubia*)
 EC50 (3 hour): 134 mg/l (Algae)

BLACK & DECKER FLAT WHITE

Long Term Toxicity	NOEC (40 days): 1.39 mg/l (<i>Oncorhynchus kisutch</i>) NOEC (7 days): 0.74 mg/l (<i>Ceriodaphnia dubia</i>)
Persistence and degradability	Biodegradable
Bioaccumulative potential	The product has no potential for bioaccumulation.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable			

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Acetone	67-64-1	20-50	5000
Toluene	108-88-3	0-22.32	1000
Methyl Ethyl Ketone	78-93-3	0-7	5000
Ethyl benzene	100-41-4	0.35-0.759	1000

SARA 311/312 - Hazard Categories:

Fire Sudden Release Reactivity Immediate (acute) Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
Toluene	108-88-3	0-22.32
Ethyl benzene	100-41-4	0.35-0.759

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
Toluene	108-88-3	Developmental, Female Reproductive
Ethyl benzene	100-41-4	Cancer

*Trace to none.

BLACK & DECKER FLAT WHITE

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: April 30,2024

Hazard Statement(s) and Risk Phrases Listed in: SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapor.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H336: May cause drowsiness or dizziness.
- H361: Suspected of damaging fertility or the unborn child.
- H373: May cause damage to organs through prolonged or repeated exposure.
- H400: Acute to aquatic life.
- H401: Toxic to aquatic life.
- H412: Harmful to aquatic life with long lasting effects.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.